Sonesse® 30 24V DC Zigbee



The Sonesse® 30 24V DC Zigbee motor increases motorized shading opportunities. It features a 2Nm powerful lifting capacity utilizing low-voltage DC power to quietly operate small profile shades and is dedicated to a variety of interior applications.

Compatible end-products







Roman



woods



shades*



Cellular shades*



Lavered/ Zebra shades



Sheer horizontals







TaHoma® pro app

Scan a unique motor QR code and follow a simple, step-by-step process to configure motor settings and end limits to save time.







Android

shades *Using CTS40

shades

Woven

Pleated



Projection screens

Main functionalities





Designed for silence



Position feedback



Openness of the **Zigbee** protocol



LED provides feedback on motor



Soft start and Soft stop



Adjustable speed



"my" function



Quick & easy settings



Built-in speed control



Mesh network router



Compatible with **HomeKit**

Benefits for professionals

Convenience

 Compatible with a wide range of interior window coverings

Easy integration

- Seamless integration to match any interior decor
- Thin round head for smooth transition into shade and tube
- Smaller light gap to minimize light leakage
- Interchangeable head color (white. black, and grey) to match fabric and hardware style and color
- Recessed interchangeable metal adaptor plate compatible with all hardware systems
- Fits small diameter tubes (suitable for an internal diameter of 31mm
- Ideal for small narrow windows to maximize viewable window area



 Low-voltage 24V DC power for safe and easy wiring

Easy programming and adjustment with TaHoma® pro





- Integrated button on the motor head allows for leaving the network and full reset
- Acts as a Zigbee® mesh network router to extend radio range
- Dedicated maintenance tool, Serv-e-Go

Reliability and services

- Highly secure protocol
- Somfy quality & warranty

Open protocol

• Native compatibility with Zigbee 3.0 controllers (including Samsung Smartthings)

Benefits for end users

Daily comfort

- Ouiet operation
- Precision motion with soft start & soft stop
- Manage natural light and privacy via timed schedules and scenes

Discreet integration and home harmony

- Smaller diameter to maximize viewable window space
- Shorter length to fit smaller windows
- White and thin round head for discreet blending (black and grey as an option)
- Low-voltage wiring that is safe and out of sight

Easy to use and maintain

- Easily control shades with the TaHoma® app
- Get real time feedback on shade positioning via a smartphone or tablet

• Hard-wired, maintenance-free

Go hands free with voice control

• Compatible with voice control assistants (with TaHoma® switch and Amazon Alexa, Google Home, or Apple HomeKit)

Safety and reliability

- No hanging cords, provides a child-safe and pet-friendly solution
- Somfy quality and warranty

Sonesse® 30 24V DC Zigbee







Item #: 1241970

Technical data

Supply Tolerance	21.6 — 26.4V DC	
Running Time	6 minutes	
Repeatability	+6°	
Cable	AWG24 — 1 Cable: 2 wire (7.5 in. Weidmüller pigtail non-removable)	
Index Protection Rating	IP30 (interior use only)	
Limit Switch Unit	Electronic	
Limit Switch Capacity	125 turns (limited to 6 minutes of rotation without stop)	
Temperature Working Range	From 32°F to 140°F (0°C to 60°C)	
Electric Insulation	Class III	
Antenna	6.9 in. (17.5cm) wire length, must not be cut or lengthened. For greatest RF range, antenna must be exposed.	
Sound Level*	<47 dB(A)*	

^{*}Noise Level: Power Level according to standards ISO3741 in dB(A) re1pW Typical Value at nominal torque without end product.

Dimensions



Cables

Weidmüller non-removable pigtail = 7.5 in. (190mm)



Optional Head Covers:



#9027133





White (supplied with motor)

#9027132

#9027134

Integrated Motor Plates (sold separately):

9025996	Sonesse 30 Motor Plate Rollease 360 R3-R8 10 x 1.8mm and screws	14
9025999	Sonesse 30 Motor Plate Acmeda 12mm and screws	8 1 p
9026003	Sonesse 30 Motor Plate Rollease Skyline and screws	25 14
9026093	Sonesse 30 Motor Plate M3 x 6mm Philips flat-head plastite screw	<u>A</u>

Performances

Nominal Torque	2Nm
Nominal Speed	25 rpm
Adjustable Speed	10 to 28 rpm (speed regulated and adjustable)
Radio Protocol	Zigbee 3.0 / Bluetooth 4.2
Radio Frequency	2.4 GHz
Nominal Voltage	24V DC
Rated Current	.625A
Standby Power	.2W

Certifications













A BRAND OF **SOMFY** GROUP