



## LT50 Range - Rapid Push Button Limits (Cont'd)

The LT50 range offers up to a 50Nm (440 in. lb.) model and a range of 14-38 rpm for all standard models, and 14 or 20 rpm for CMO versions.

MOTOR TYPE	NOMINAL TORQUE		SPEED rpm	ELECTRICAL RATING				LIMIT SWITCH CAPACITY # Rotations	WEIGHT		THEORETICAL LIFTING CAPACITY*	
	in. lb.	Nm		Volt	Hz	Ampere	Watt		lb.	kg.	lb.	kg.
515S2	132	15	38	120	60	1.8	210	46	5.62	2.55	132	60
515S2RH	132	15	38	120	60	1.8	210	46	5.62	2.55	132	60
515A2	132	15	20	120	60	1.1	130	46	4.3	1.95	132	60
520R2	176	20	14	120	60	1.1	130	46	4.3	1.95	176	80
525A2	220	25	20	120	60	1.6	180	46	4.74	2.15	220	100
525A2 CMO	220	25	20	120	60	1.6	180	34	7.14	3.24	220	100
530R2	264	30	14	120	60	1.5	170	46	4.74	2.15	264	120
530R2 CMO	264	30	14	120	60	1.5	170	34	7.14	3.24	264	120
535A2	308	35	20	120	60	2.1	250	46	5.62	2.55	308	140
535A2 CMO	308	35	20	120	60	2.1	250	34	7.69	3.49	308	140
540R2	352	40	14	120	60	1.8	210	46	5.62	2.55	352	160
540R2 CMO	352	40	14	120	60	1.8	210	34	7.69	3.49	352	160
550R2	440	50	14	120	60	2.1	250	46	5.62	2.55	440	200
550R2 CMO	440	50	14	120	60	2.1	250	34	7.69	3.49	440	200

## SLT (for Cassette Awnings) - Star Head Rapid Push Button Limits

MOTOR TYPE	NOMINAL TORQUE		SPEED rpm	ELECTRICAL RATING				LIMIT SWITCH CAPACITY # Rotations	WEIGHT		THEORETICAL LIFTING CAPACITY*	
	in. lb.	Nm		Volt	Hz	Ampere	Watt		lb.	kg.	lb.	kg.
525A2 SLTL	220	25	20	120	60	1.6	180	46	5.5	2.5	220	100
525A2 SLTR	220	25	20	120	60	1.6	180	46	5.5	2.5	220	100
535A2 SLTL	308	35	20	120	60	2.1	250	46	6.4	2.9	308	140
535A2 SLTR	308	35	20	120	60	2.1	250	46	6.4	2.9	308	140
660R2 SLTL	530	60	14	120	60	2.5	285	35	9.7	4.4	424	192
660R2 SLTR	530	60	14	120	60	2.5	285	35	9.7	4.4	424	192

L=Left Mount R=Right Mount

## ILT - Electronic Limit Switch

MOTOR TYPE	NOMINAL TORQUE		SPEED rpm	ELECTRICAL RATING				LIMIT SWITCH CAPACITY # Rotations	WEIGHT		THEORETICAL LIFTING CAPACITY*	
	in. lb.	Nm		Volt	Hz	Ampere	Watt		lb.	kg.	lb.	kg.
506S2 ILT	52	6	38	120	60	.95	110	300	4.6	2.07	52	23.6
506S2 ILTRH	52	6	38	120	60	.95	110	300	4.6	2.07	52	23.6
515S2 ILT	132	15	38	120	60	1.8	210	300	6.1	2.77	132	60
515S2 ILTRH	132	15	38	120	60	1.8	210	300	6.1	2.77	132	60
535A2 ILT	308	35	20	120	60	2.1	250	300	6.1	2.77	308	140
535A2 ILTRH	308	35	20	120	60	2.1	250	300	6.1	2.77	308	140

\* Please refer to Definition of Theoretical Lifting Capacity on page 13.